TRUST AND CREDIBILITY

AGRICULTURAL SPRAYERS LOW COST / HIGH BENEFITS

PRODUCTS CATALOG - 2024



ABOUT US



- solutions for agricultural implements.
- The company is 100% Brazilian.
- states.
- in South America, Central America and Africa;

www.imep.ind.br

Pompéia, São Paulo, Brazil!

• Founded on October 16, 1973, IMEP has over 50 years of tradition in

• It currently has 154 employees and an area of 18,000m².

• Located 450 km from the capital of Brazil's highest GDP state, São Paulo, and 550 km from the port of Santos. Strategically located in the west of the state of São Paulo, close to the main agricultural producing

• In addition to the domestic market, the company operates commercially

• It has a broad portfolio of solutions for sprayers and implements, as well as manufacturing and selling spare parts and polyethylene tanks.

@imep.a

COST BENEFIT POSITIONING

ECONOMIC LINE SPRAYERS

We offer smaller farmers and family farmers a range of sprayers that can be attached to the 3rd point of the tractor, with top-of-the-range components and an epoxy-painted chassis structure, with piston pumps and high-performance spray nozzles/points.



www.imep.ind.br



@imep.agricola

BOOMSECOMAXX-10X ENTRY-LEVEL SPRAYER, LOW COST AND EASY TO

HANDLE AND MAINTAIN.




TECHNICAL SPECIFICATIONS

Booms:

- Length (m) : 10.00
- Spacing between nozzles (cm): 50
- Nozzles: monojet.
- Lift and unlock system

- Available capacities (I): 300 / 400 / 600 and 800.



TECHNICAL SPECIFICATIONS

- Length (m) : 9.50 / 12 / 14
- Spacing between nozzles (cm): 50
- Nozzles: monojet.
- Lift cable and pulley system.
- Hose branches.
- Working height of 0.50 to 1.50m from the ground. Chemical circuit:
 - Control valve: DL02 manual.
 - Stirrer: Hydraulic.
 - Ceramic-sleeves piston pump: 75 l/min.
 - PTO: 540 rpm.
 - Main Filter 100 l/min.
 - In-line filters.
 - Optional: Filler unit
 - Available capacities (I): 300 / 400 / 600 / 800. • Material: Polyethylene - black color. • Clean water tank: 15 liters. Main tank strainer with bottle washer.



BOOMSECOMAXX-THOR Booms: HYDRAULICALLY DRIVEN BOOM SPRAYER WITH MANUAL OR ELECTRIC CONTROLLER. PRECISION AGRICULTURE TECHNOLOGY AVAILABLE **3RD TRACTOR POINT EPOXY PAINTING** 306-400 / 356-450 / Weight (empty) Chemical circuit: 506-550 kg 3.10 m Height 1.60 m Length 2.00 m (closed booms) Width **AVAILABLE** • In-line filters **OPTIONS** • Filler unit Tank:

www.imep.ind.br

TECHNICAL SPECIFICATIONS

- Length (m) : 12 / 14 / 16 / 18
- Spacing between nozzles (cm): 50
- Nozzles: Bijet antigotejo nozzle holder (JCVI-01 / LBDI-110°)
- Hydraulic boom control (manual / levers) and "unlock" antiimpact system.
- Stainless steel branches
- Working height of 0.50 to 1.70m from the ground.
- Control valve: VAR 02-way.
- Optional: Masterflow Manual or Electric 04-way ARAG.
- Stirrer: Hydraulic.
- Ceramic-sleeves piston pump: 75 / 100 l/min (for the 18m boom version).
- PTO: 540 rpm.
- Main filter 100 l/min.

- **Optional:** Agrochemical mixer kit with bottle wash 20 liters.
- Available capacities (I): 600 / 800 / 1000.
- Material: Polyethylene gray color.
- Clean water tank: 15 liters.
- Main tank strainer with bottle washer.

<u>@imep.agricola</u>

LIVESTOCK ECOPEC SPRAYER FOR PASTURE PEST CONTROL, WITH TOP-OF-THE-RANGE COMPONENTS, EASY TO USE AND MAINTAIN.

3RD TRACTOR POINT EPOXY PAINTING

Weight (empty)	198kg
Height	2.35m
Length	1.50 m
Width	1.35 m

OPTIONAL



www.imep.ind.br

Booms:

- ground.

Chemical circuit:

- IMEP.

- Tank:

TECHNICAL SPECIFICATIONS

• Boom length (m): 2.20 • Height settings (m): from 0.50 m to 2.25 m above the • Nozzles: MJE / TK. • Opening with shock absorbers. • Working range: 12m. • Hose reel: 2 units • Spray lance: 2 units. • Control valve: manual CI 02-way / DL 02-way Model • Stirrer: Hydraulic. • Ceramic-sleeves piston pump: 75 l/min. • PTO: 540 rpm. • Main filter 100 l/min. • **Optional:** Filler unit

• Available capacities (I): 300 / 400 / 600 / 800. • Material: Polyethylene • Clean water tank: 15 liters. • Main tank strainer with bottle washer.



AGRICULTURAL ECOHUSKY LANCE / NOZZLE **TECHNICAL SPECIFICATIONS** SPRAYER FOR LOCALIZED CONTROL OR FOR CLEANING

FARMS, HOSES AND SHEDS, WITH TOP-OF-THE-RANGE COMPONENTS, EASY TO HANDLE AND MAINTAIN.

3RD TRACTOR POINT EPOXY PAINTING

www.imep.ind.br

Weight (empty)	140 - 170 kg
Height	1.80 m
Length	1.50 m
Width	1.35 m

- Hose length (m): 12 • Number of lances or nozzles: 02.
 - Reels: 02.
- Control valve: manual DL 02-way.
- Stirrer: Hydraulic.
- Ceramic-sleeves piston pump: 75 l/min.
- PTO: 540 rpm.

Tank:

- Available capacities (I): 300 / 400 / 600 / 800.

Lances and nozzles:

Chemical circuit:

• Main filter 100 l/min.

- Material: Polyethylene color black
- Clean water tank: 15 liters.
- Main tank strainer with bottle washer.

Other versions / Adaptable options:

• Lance or nozzle / livestock kit.

@imep.agricola

AGRICULTURAL ECOHUSKY

SPRAYER FOR LOCALIZED CONTROL OR FOR CLEANING FARMS, HOSES AND SHEDS, WITH TOP-OF-THE-RANGE COMPONENTS, EASY TO HANDLE AND MAINTAIN.

3RD TRACTOR POINT EPOXY PAINTING

Weight (empty)	140 - 170 kg
Height	1.80 m
Length	1.50 m
Width	1.35 m



- Hose length (m): 12 • Number of spray guns: 02.
- Reels: 02.
- Stirrer: Hydraulic.
- Ceramic-sleeves piston pump: 75 l/min.

Tank:

- Material: Polyethylene color black
- Clean water tank: 15 liters.
- Main tank strainer with bottle washer.

Other versions / Adaptable options:

• Lance or nozzle / livestock kit.

www.imep.ind.br

TECHNICAL SPECIFICATIONS SPRAY GUN

Spray Gun / Spear and nozzle:

Chemical circuit:

- Control valve: 02-way VAR manual.
- PTO: 540 rpm.
- Main filter 100 l/min.

• Available capacities (I): 300 / 400 / 600 / 800.

@imep.agricola

TURBO ATOMIZERS ECOTHUNDER

SPRAYER FOR PEST CONTROL IN COFFEE, CITRUS AND FRUIT TREES. THE SENSATION OF THE MARKET! ONLY SUPPLIED WITH STANDARD COMPONENTS FROM THE ECONOMY LINE. **3RD TRACTOR POINT**

EPOXY PAINTING

Weight (empty)	170 - 210 kg
Height	1.50 m
Length	1.75 m
Largura	1.10 to 1.35 m



Turbine:

Chemical circuit:

Tank:



www.imep.ind.br

TECHNICAL SPECIFICATIONS

• Deflector material: fiberglass • Diameter: 750mm with safety lock. • Number of nozzles on the branches: 16. • Nozzles: Anti-drip nozzle holder cone JCVI-02. Individual closure of the nozzle holders. • Brass branches. • RPM: 1800 rpm (PTO: 540 rpm) • Air volume: $10 \text{ m}^3/\text{s}$ • Control valve: 02-way VAR manual. • Ceramic-sleeves piston pump: 75 l/min. • PTO: 540 rpm. • Main filter 100 l/min. • Stirrer: Hydraulic.

• Available capacities (I): 300 / 400 / 600 / 800. • Material: polyethylene - color black • Clean water tank: 15 liters. • Main tank filter with spray bottle washer.



AISLERS AGRICULTURAL /HERBICIDE ECOVING

SPRAYER FOR APPLYING HERBICIDE TO CONTROL PESTS IN COFFEE, CITRUS, FRUIT AND FORESTRY PLANTATIONS. ONLY SUPPLIED WITH STANDARD COMPONENTS FROM THE ECONOMY LINE.

3RD TRACTOR POINT

EPOXY PAINTING

200 to 250kg Weight (empty) Height 1.65m Length 1.75m 1.75m (Retracted wings) Width 2.90 (open wings)

www.imep.ind.br



TECHNICAL SPECIFICATIONS

Protective wings:

- Material: Polyethylene and steel structure.
- Number of nozzles: 4.
- Nozzles: Flat Fan.
- Application range up to 2.90m wide.

Chemical circuit:

- Control valve: DL 03-way manual.
- Ceramic-sleeves piston pump: 75 l/min.
- Main filter 100 l/min.
- Stirrer: Hydraulic.


Tank:

- Available capacities (I): 300 / 400 / 600 / 800.
- Material: polyethylene color black
- Clean water tank: 15 liters.
- Main tank filter with spray bottle washer.



OUR CUSTOMER SERVICES CHANNELS +55 14 3405-1400 / +55 14 99669-0143 🕓 www.imep.ind.br imep@imep.ind.br @imep.agricola Know our spraying nozzles

SEE MORE, OUR BOOMS AND AIR BLAST SPRAYERS WITH HIGH PERFORMANCE AND AGRICULTURAL PRECISION TECNOLOGY TO GRAIN/CEREALS AND SUGAR-ENERGY, CROP TREES AND LIVESTOCK



Av Industrial, 200 - Industrial Distritct - Pompéia - São Paulo - Brazil